





	DIMENSIONS			BASE MODEL NO.	ADD LAMP CODE	ADD FINISH CODE
	W	H	X			
	10-1/2"	48"	33"	<b>S2430</b>	3F017 <i>(No Downlight)</i> 3F017-M39 <i>(M39 Downlight)</i> 3F017-75PAR30 <i>(PAR30 Downlight, 120V only)</i>	BA, BN, PT
	10-1/2"	84"	57"		<b>S2431</b>	
	10-1/2"	144"	105"	<b>S2432</b>		3F059 <i>(No Downlight)</i> 3F059-M39 <i>(M39 Downlight)</i> 3F059-75PAR30 <i>(PAR30 Downlight, 120V only)</i>

**ORDERING INFORMATION**

Order as a Complete Unit: Model No. + Lamp Code + Finish Code + Option Code + Voltage

TECHNICAL SPECIFICATIONS	FINISHES	OPTIONS
<b>Ballast:</b> High Power Factor, Electronic, 120/277 <b>Mounting:</b> Mounts to Standard Electrical Junction Box (by others) Structural Blocking with a 4" Octagonal Junction Box (by others) is required.	<b>BA</b> Brushed Aluminum <b>BN</b> Brushed Nickel <b>PT</b> Painted Finishes - (Specify Color Code from Our Standard Finish Chart)	<b>EM</b> Emergency Battery Pack with Fluorescent Lighting (Remote) <b>OA</b> Specify Overall Height of Fixture in Inches; E.G. - OA48 <b>DIM</b> Dimmable Integral Ballast (Consult Factory) <b>SWC</b> 45-Degree Swivel Canopy

LAMPING	FEATURES
<b>F017</b> = 17 Watt T8 Lamp, Med Bi-Pin <b>F032</b> = 32 Watt T8 Lamp, Med Bi-Pin <b>F059</b> = 59 Watt T8 Lamp, Med Bi-Pin <b>M39</b> = 39 Watt Metal Halide PAR 20 <b>75 PAR 30</b> = 75 Watt PAR 30, Medium Base	<ul style="list-style-type: none"> <li>● Sandblasted Acrylic</li> <li>● Single Stem with Hang Straight Swivel</li> <li>● Downlight on Separate Circuit</li> <li>● Integral Electronic Ballast</li> <li>● Solid Aluminum Top &amp; Bottom Cylinder</li> </ul>

