




DIMENSIONS



W	H	X	BASE MODEL NO.
22"	36"	4 3/4"	S2000-L48
26"	36"	5"	S2001-L48
30"	36"	5 1/4"	S2002-L60

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Solid Metal Indirect Bowl
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Finish Code + Option Code

S2000-L48	+	27K	+	<u>PT</u>	+	OA	+	Option
S2001-L48		30K		<u>XT</u>				
S2002-L60		35K		<u>PF</u>				
		40K						

FINISHES

XT Trending Brushed Metal Finishes*

PF Pure Metal Finishes*

PT Powder Coated Finishes*

*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)

SWC 35-Degree Swivel Canopy

LIGHT OUTPUT – INDIRECT ONLY

LXX = ~ 90 LPW Delivered Lumens (Example: L48= 48W x 90LPW = 4,320 Lumens)