




DIMENSIONS



| W | H | X | BASE MODEL NO. |
|-----|-----|--------|------------------|
| 10" | 36" | 7" | S2030-L12 |
| 14" | 36" | 9 1/2" | S2031-L14 |
| 18" | 36" | 11" | S2032-L24 |
| 18" | 36" | 11" | S2032-L39 |
| 18" | 36" | 11" | S2032-L52 |

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Glass Diffuser
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Finish Code + Option Code

| | | | | | | | | |
|-----------|---|-----|---|----|---|----|---|--------|
| S2030-L12 | + | 27K | + | PT | + | OA | + | Option |
| S2031-L14 | | 30K | | XT | | | | |
| S2032-L24 | | 35K | | PE | | | | |
| S2032-L39 | | 40K | | | | | | |
| S2032-L52 | | | | | | | | |

FINISHES

XT Trending Brushed Metal Finishes*

PF Pure Metal Finishes*

PT Powder Coated Finishes*

*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)

SWC 35-Degree Swivel Canopy

LIGHT OUTPUT

LXX = ~ 100 LPW Delivered Lumens (Example: L12= 12W x 100LPW = 1,200 Lumens)