




DIMENSIONS



W	H	X	BASE MODEL NO.
10"	36"	6"	S2040-L12
14"	36"	9 1/2"	S2041-L14
18"	36"	12 1/2"	S2042-L24

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Glass Diffuser
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Finish Code + Option Code

S2040-L12	+	27K	+	PT	+	OA	+	Option
S2041-L14		30K		XT				
S2042-L24		35K		PF				
		40K		CC				

FINISHES

XT Trending Brushed Metal Finishes*

PF Pure Metal Finishes*

PT Powder Coated Finishes*

CC Custom Painted Finish

*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)

SWC 35-Degree Swivel Canopy

LIGHT OUTPUT

LXX = ~ 100 LPW Delivered Lumens (Example: L12= 12W x 100LPW = 1,200 Lumens)