


# S2170 Series

## Pyramid



### DIMENSIONS



W	H	X	BASE MODEL NO.
25"	36"	7 1/2"	<b>S2170-L60</b>
36"	42"	11"	<b>S2171-L72</b>
48"	48"	14 1/2"	<b>S2172-L108</b>

### SPECIFICATIONS

**Driver:** 0-10V dimming to 1%, 120/277

**Mounting:** Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

### FEATURES

- Opal Matte Acrylic (Bottom Dome)
- LED 0-10V Dimming Driver

### ORDER AS A COMPLETE UNIT:

Model No.	+ Lamp Code	+ Finish Code	+ OA	+ Option Code
S2170-L60	+ 27K	+ PT	+ OA	+ Option
S2171-L72	30K			
S2172-L108	35K			
	40K			

### FINISHES

PT Powder Coated Finishes\*

\*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

### OPTIONS

**BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.

**EML** Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)

**SWC** 35-Degree Swivel Canopy (Single Stem Only)

**NAD** No Acrylic Diffuser – Solid Housing

**DAD** Divided Acrylic Diffuser



No Acrylic Diffuser Option



Divided Acrylic Diffuser

### LIGHT OUTPUT

LXX = ~ 69 LPW Delivered Lumens (Example: L60= 60W x 69LPW = 4,140 Lumens)