




DIMENSIONS



W	H	X	BASE MODEL NO.
23"	48"	6 1/8"	S2255-L120
30"	48"	6 1/8"	S2256-L120

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Matte Acrylic
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Finish Code + OA + Option Code
 S2255-L120 + 27K + PT + OA + Option
 S2256-L120 30K
 35K
 40K

FINISHES

PT Powder Coated Finishes*

*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)

SWC 35-Degree Swivel Canopy

1SAC Single Stem with Aircraft Cables

CN Chain and Power Cord Mount

2C Two-Circuit Wiring

NP1 120V NEMA Plug w/3 Connector Cord

NP2 277V NEMA Plug w/3 Connector Cord

LIGHT OUTPUT

LXX = ~ 81 LPW Delivered Lumens (Example: L120= 120W x 81LPW = 9,720 Lumens)