




DIMENSIONS



W	H	X	BASE MODEL NO.
13"	36"	20"	S2270-L32

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Matte Acrylic Cylinder
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No.	+ Lamp Code	+ CCT	+ Finish	+ Fabric	+ OA	+ Option Code
S2270-L32	+ 27K	+ 30K	+ <u>PT</u>	+ OA	+ Option	
			+ <u>XT</u>			
			+ <u>PE</u>			
			+ 35K			
			+ 40K			

FINISHES

PT Powder Coated Finishes*

XT Trending Brushed Metal Finishes*

PF Pure Metal Finishes*

*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup

OA Specify Overall Height of Fixture in Inches; E.G. – OA48

FAA Faux Alabaster Acrylic (Hand Painted) [FA1 White; FA2, Antique; FA3 Grey; FA4 Taupe; FA5 Honey, FA6 Tuscan]

SWC 35-Degree Swivel Canopy (Single Stem Only)

LIGHT OUTPUT

LXX = ~ 65 LPW Delivered Lumens (Example: L32= 32W x 65LPW = 2,080 Lumens)