




## DIMENSIONS



W	H	X	BASE MODEL NO.
24"	24"	6"	<b>S2280-L60</b>
30"	24"	6"	<b>S2281-L72</b>
36"	24"	6"	<b>S2282-L84</b>

## SPECIFICATIONS

**Driver:** 0-10V dimming to 1%, 120/277

**Mounting:** Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

## FEATURES

- Opal Matte Acrylic
- LED 0-10V Dimming Driver

## ORDER AS A COMPLETE UNIT:

**Model No. + Lamp Code + Finish Code + OA + Option Code**

S2280-L60	+	27K	+	PT	+	OA	+	Option
S2281-L72		30K		XT				
S2282-L84		35K		PF				
		40K						

## FINISHES

**PT** Powder Coated Finishes\*

**XT** Trending Brushed Metal Finishes\*

**PF** Pure Metal Finishes\*

\*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

## OPTIONS

**BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.

**EML** Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)

**FAA** Faux Alabaster Acrylic (Hand Painted) [FA1 White; FA2 Antique; FA3 Grey; FA4 Taupe; FA5 Honey; FA6 Tuscan]

**SWC** 35-Degree Swivel Canopy

**2C** Two-Circuit Wiring

**TPL** Top Lens, Opal Acrylic

## LIGHT OUTPUT

**LXX** = ~ 85 LPW Delivered Lumens (Example: L60= 60W x 85LPW = 5,100 Lumens)