




## DIMENSIONS



W	H	X	BASE MODEL NO.
26"	24"	5 7/8"	<b>S2310-L60</b>
36"	36"	7 1/2"	<b>S2311-L72</b>
42"	36"	8"	<b>S2312-L108</b>
48"	36"	10"	<b>S2313-L120</b>
60"	48"	15"	<b>S2314-L144</b>

## SPECIFICATIONS

**Driver:** 0-10V dimming to 1%, 120/277

**Mounting:** Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

## FEATURES

- Opal Matte Acrylic
- LED 0-10V Dimming Driver

## ORDER AS A COMPLETE UNIT:

Model No.	+ Lamp Code	+ Finish Code	+ OA	+ Option Code
S2310-L60	27K	PT	OA	Option
S2311-L72	30K	XT		
S2312-L108	35K	PE		
S2313-L120	40K			
S2314-L144				

## FINISHES

**PT** Powder Coated Finishes\*

**XT** Trending Brushed Metal Finishes\*

**PF** Pure Metal Finishes\*

\*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

## OPTIONS

**BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.

**EML** Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)

**FAA** Faux Alabaster Acrylic (Hand Painted) [FA1 White; FA2 Antique; FA3 Grey; FA4 Taupe; FA5 Honey; FA6 Tuscan]

**SWC** 35-Degree Swivel Canopy

**2C** Two-Circuit Wiring

## LIGHT OUTPUT

**LXX** = ~ 119 LPW Delivered Lumens (Example: L60= 60W x 119LPW = 7,140 Lumens)