


DIMENSIONS



W	H	X	BASE MODEL NO.
28"	24"	6 1/4"	S2325-L36
36"	30"	8 1/4"	S2326-L60
42"	36"	9 1/4"	S2327-L84
48"	42"	10 1/4"	S2328-L108

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Matte Acrylic (Standard)
- Fabricated Heavy Gauge Cold Rolled Steel
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Finish Code + OA + Option Code

S2325-L36	+	27K	+	PT	+	OA	+	Option
S2326-L60		30K		XT				
S2327-L84		35K		CC				
S2328-L108		40K						

FINISHES

PT Powder Coated Finishes*

XT Trending Brushed Metal Finishes*

CC Custom Painted Finish

*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)

FAA Faux Alabaster Acrylic (Hand Painted) [FA1 White; FA2 Antique; FA3 Grey; FA4 Taupe; FA5 Honey; FA6 Tuscan]

SWC 35-Degree Swivel Canopy

2C Two-Circuit Wiring

LIGHT OUTPUT

LXX = ~ 69 LPW Delivered Lumens (Example: L36= 36W x 69LPW = 2,484 Lumens)