




DIMENSIONS



W	H	X	BASE MODEL NO.
24"	36"	6 1/2"	S2345-L36
30"	36"	7 1/2"	S2346-L42
36"	48"	8 1/2"	S2347-L60

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) with Hardware Provided

FEATURES

- Opal Matte Acrylic Bottom Lens
- Direct/Indirect Light Distribution
- Solid Spun Aluminum Shade (Seamless)
- Clear Silver Braided Cord
- 5/8" Tube with Aircraft Cable
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Finish Code + Option Code
 S2345-L36 + 30K + PT + Option
 S2346-L42 + 35K + XT
 S2347-L60 + 40K

FINISHES

PT Powder Coated Finishes*

XT Trending Brushed Metal Finishes*

*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup

OA Specify Overall Height of Fixture in Inches; E.G. – OA48

2C Two-Circuit Wiring

1S Single Stem

TPL Top Lens, Opal Acrylic

BK3 Black Cord with (3) Adjustable Aircraft Cables

WH3 White Cord with (3) Adjustable Aircraft Cables

LIGHT OUTPUT†

LXX = ~ 75 LPW Delivered Lumens (Example: L36= 36W x 75LPW = 2,700 Lumens)