


# S2425 Series

Indra 6



## DIMENSIONS



W	X	H	BASE MODEL NO.
6"	11"	36"	<b>S2420-L24</b> (Stem)
6"	11"	36"	<b>S2425-L24</b> (Cables)

## SPECIFICATIONS

**Driver:** 0-10V dimming to 1%, 120/277

**Mounting:** Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

## FEATURES

- Clear Silver Electrical Cord with (2) Adjustable Aircraft Cables or Single Stem
- Opal Matte Glass with Closed Bottom
- LED 0-10V Dimming Driver

## ORDER AS A COMPLETE UNIT:

Model No.	+ Lamp Code	+ CCT	+ Finish	+ Fabric	+ OA	+ Option Code		
S2420-L24	+	27K	+	PT	+	OA	+	Option
S2425-L24		30K		XT				
		35K		PF				
		40K						

## FINISHES

**PT** Powder Coated Finishes\*

**XT** Trending Brushed Metal Finishes\*

**PF** Pure Metal Finishes\*

\*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

## OPTIONS

**BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.

**EML** Remote 10W Emergency LED Battery Backup

**OA** Specify Overall Height of Fixture in Inches; E.G. – OA48

**SWC** 35-Degree Swivel Canopy

**OMA** Opal Matte Acrylic with Closed Bottom

## LIGHT OUTPUT

**LXX** = ~ 70 LPW Delivered Lumens (Example: L24= 24W x 70LPW = 1,680 Lumens)

