


S2430 Series

Grand Cylinder



DIMENSIONS



W	H	X	BASE MODEL NO.
10 1/2"	48"	33"	S2430-L24
10 1/2"	84"	57"	S2431-L48
10 1/2"	144"	105"	S2432-L96

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277 for both Cylinder and Downlight (2 Zone Control Optional)

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Matte Acrylic
- Single Stem with Hang Straight Swivel
- Downlight and Cylinder Core May Be Wired to Separate Control Circuits
- Solid Aluminum Top & Bottom Cap
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Downlight + Lamp Code + Finish Code + OA + Option Code

S2430-L24	+	___*	+	27K	+	PT	+	OA	+	Option
S2431-L48		D16N		30K		XT				
S2432-L96		D16M		35K						
		D16W		40K						

___* = if left blank – no downlight

FINISHES

PT Powder Coated Finishes*

XT Trending Brushed Metal Finishes*

*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

DOWNLIGHT OPTIONS

D16N Narrow (30 degrees)

D16M Medium (45 degrees)

D16W Wide (60 degrees)

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)

SWC 35-Degree Swivel Canopy

SB1 Clear Silver Braided Cord with One Adjustable Aircraft Cable

LIGHT OUTPUT

Cylinder Core Lighting Lumens: LXX = LED Wattage, therefore L24 = LED 24W. The typical lumen output is ~89LPW, so therefore L24 would deliver 2,136L. Use this formula to estimate delivered lumens based on the LXX number for each length.

Downlight Lumens: DxxW indicates Downlight wattage and beam spread. For the downlight, typical lumen output is 100LPW, so a D12W would deliver 1,200L in a wide beam pattern.