


S2440 Series

Grand Ring



DIMENSIONS



W	H	X	BASE MODEL NO.
24"	72"	9 3/4"	S2440-L48
30"	72"	11 3/4"	S2441-L64
36"	72"	13 3/4"	S2442-L72

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) with Hardware Provided

FEATURES

- Opal Matte Acrylic Sloped Interior Lens
- Clear Silver Braided Cord with (3) Adjustable Aircraft Cables
- Seamless Aluminum Housing
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No.	+ Lamp Code	+ Finish Code	+ Option Code
S2440-L48	+ 30K	+ PT	+ Option
S2441-L64	+ 35K	+ XT	
S2442-L72	+ 40K		

FINISHES

PT Powder Coated Finishes*

XT Trending Brushed Metal Finishes*

*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup

OA Specify Overall Height of Fixture in Inches; E.G. – OA48

BK3 Black Cord with (3) Adjustable Aircraft Cables

WH3 White Cord with (3) Adjustable Aircraft Cables

LIGHT OUTPUT

LXX = ~ 68 LPW Delivered Lumens (Example: L48= 48W x 68LPW = 3,264 Lumens)