




DIMENSIONS



W	H	X	BASE MODEL NO.
13"	42"	29"	S2480-L24M
15"	42"	29"	S2481-L24M

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Matte Acrylic Bottom Diffuser
- Fabric Shades on Heavy Translucent White Styrene
- Single Stem
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No.	+ Lamp Code	+ CCT	+ Finish	+ Fabric	+ OA	+ Option Code
S2480-L24M	+ 27K	+ <u>PT</u>	+ LF01	LF08	+ OA	+ Option
S2481-L24M	30K	<u>XT</u>	LF02	LF09		
	35K	<u>PF</u>	LF03	LF10		
	40K		LF04	LF11		
			LF05	LF12		
			LF05	LF13		
			LF07	LF14		

FINISHES

PT Powder Coated Finishes*

XT Trending Brushed Metal Finishes*

PF Pure Metal Finishes*

*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

FABRIC

LF01 Huggy White	LF02 Olive
LF03 Sage	LF04 Orchre
LF05 Praline	LF07 Canvas
LF08 Butter	LF09 Breeze
LF10 Ebony	LF11 Parchment
LF12 Flan	LF13 Natural HF
LF14 Merlot	
CLF Custom Linen Fabric Shade (Consult Factory)	

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup

OA Specify Overall Height of Fixture in Inches; E.G. – OA48

SB2 Clear Silver Braided Cord with (2) Adjustable Aircraft Cables

LIGHT OUTPUT – (VARIES WITH SHADE COLOR)

LXX = ~ 60 LPW Delivered Lumens (Example: L24= 24W x 60LPW = 1,440 Lumens)[White Shade – LF01]