




DIMENSIONS



W	H	X	BASE MODEL NO.
10"	84"	52"	S2500-L64

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277 [Excluding Downlight]
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Matte Acrylic
- Single Stem
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Finish + OA + Option Code

S2500-L64	+	27K	+	PT	+	OA	+	Option
		30K		BA				
		35K		BB				
		40K		BN				

FINISHES

BA Brushed Aluminum **BN** Brushed Nickel
BB Brushed Brass **PT** Painted Finishes*
 *(Specify Color Code from the list of Powdercoat finishes [except interior only metallics])

OPTIONS

EML Emergency Battery Pack with LED Lighting (Remote – Requires Additional Power Cable)
FAA = Faux Alabaster Acrylic (Hand Painted) (FA-1 White; FA-2 Antique; FA-3 Grey; FA-4 Taupe; FA-5 Honey; FA-6 Tuscan)
SWC 35- Degree Swivel Canopy
2C Two-Circuit Wiring
SB1 Clear Silver Braided Cord with (1) Adjustable Aircraft Cable
75PAR30 75 Watt Par 30, Medium Base Halogen Downlight

LIGHT OUTPUT

LXX = ~ 83 LPW Delivered Lumens (Example: L64= 64 x 83 = 5,312 Lumens)