




DIMENSIONS



W	H	X	BASE MODEL NO.
13"	42"	28"	S2520-L68

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277 [Excluding Downlight]
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) with Hardware Provided

FEATURES

- Opal Matte Acrylic
- 150 Watt PAR 38 Medium Base-Downlight Standard on Separate 120V Only Circuit
- Solid Bar Stock Material
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Finish Code + OA + Option Code
 S2520-L68 + 27K + PT + Option
 30K + XT
 35K
 40K

FINISHES

PT Powder Coated Finishes*
XT Trending Brushed Metal Finishes*
 *(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.
EML Remote 10W Emergency LED Battery Backup
OA Specify Overall Height of Fixture in Inches; E.G. – OA48
FAA = Faux Alabaster Acrylic (Hand Painted) (FA1 White; FA2 Antique; FA3 Grey; FA4 Taupe; FA5 Honey; FA6 Tuscan)
SWC 35-Degree Swivel Canopy
2C = Two-Circuit Wiring

LIGHT OUTPUT

LXX = ~ 69 LPW Delivered Lumens (Example: L68= 68W x 69LPW = 4,692 Lumens)