




DIMENSIONS



W	H	X	BASE MODEL NO.
13"	42"	28"	S2520-L68

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277 [Excluding Downlight]
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) with Hardware Provided

FEATURES

- Opal Matte Acrylic
- 150 Watt PAR 38 Medium Base-Downlight Standard on Separate 120V Only Circuit
- Solid Bar Stock Material
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Finish Code + OA + Option Code

S2520-L68	+	27K	+	PT	+	Option
		30K		BA		
		35K		BB		
		40K		BN		

FINISHES

BA Brushed Aluminum **BN** Brushed Nickel
BB Brushed Brass **PT** Powder Coated Finishes*
 *(Specify Color Code from the list of Powder Coating Finishes)

OPTIONS

EML Emergency Battery Pack with LED Lighting (Remote)
OA Specify Overall Height of Fixture in Inches; E.G. - OA48
FAA = Faux Alabaster Acrylic (Hand Painted) (FA1 White; FA2 Antique; FA3 Grey; FA4 Taupe; FA5 Honey; FA6 Tuscan)
SWC 35-Degree Swivel Canopy
2C = Two-Circuit Wiring

LIGHT OUTPUT

LXX = ~ 69 LPW Delivered Lumens (Example: L68= 68 x 69 = 4,692 Lumens)