




DIMENSIONS



W	H	X	BASE MODEL NO.
11"	42"	29"	S2525-L32
13"	48"	31"	S2526-L32

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277 [Excluding Downlight]

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) Structural Blocking with a 4" Octagonal Junction Box (by others) is required.

FEATURES

- Opal Matte Acrylic
- 150W Par38 Medium Base Downlight on Separate 120V Only Circuit
- Solid Bar Stock Material
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Finish + OA + Option Code
 S2525-L32 + 27K + PT + OA + Option
 S2526-L32 + 30K + XT + OA + Option
 + 35K + PF + OA + Option
 + 40K + OA + Option

FINISHES

PT Powder Coated Finishes*

XT Trending Brushed Metal Finishes*

PF Pure Metal Finishes*

*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup

OA Specify Overall Height of Fixture in Inches; E.G. – OA50

FAA = Faux Alabaster Acrylic (Hand Painted) (FA1 White; FA2 Antique; FA3 Grey; FA4 Taupe; FA5 Honey; FA6 Tuscan)

SWC 35-Degree Swivel Canopy

LIGHT OUTPUT

LXX = ~ 68 LPW Delivered Lumens (Example: L32= 32W x 68LPW = 2,176 Lumens)