




SUPERCEDED BY S2B60 SERIES

This product is still available to complete existing specifications, quotes, bids and active orders.
Please use the new part number for new applications and specifications.

DIMENSIONS



W	H	X	BASE MODEL NO.
6"	96"	24"	S2530-L24
6"	96"	36"	S2531-L34
6"	96"	48"	S2532-L48
6"	96"	72"	S2533-L72
6"	144"	96"	S2534-L96

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277 [Excluding Downlight]
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) with Hardware Provided

FEATURES

- Opal Matte Acrylic Cylinder
- Clear Silver Braided Cord with (1) Adjustable Aircraft Cable
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No.	+ Lamp Code	+ Finish	+ OA	+ Option Code
S2530-L24	27K	PT	OA	Option
S2531-L34	30K	XT		
S2532-L48	35K			
S2533-L72	40K			
S2534-L96				

FINISHES

PT Powder Coated Finishes*
XT Trending Brushed Metal Finishes*
*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

- BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.
- EML** Remote 10W Emergency LED Battery Backup
- OA** Specify Overall Height of Fixture in Inches; E.G. – OA48
- SWC** 45-Degree Swivel Canopy
- 1S** Single Stem
- P30** Optional E26 Socket for LED PAR30 Shortneck Downlight, 120V Only Separate Circuit

LIGHT OUTPUT

LXX = ~ 83 LPW Delivered Lumens (Example: L24= 24W x 83LPW = 1,992 Lumens)