




SUPERCEDED BY S2B70 SERIES

This product is still available to complete existing specifications, quotes, bids and active orders.
Please use the new part number for new applications and specifications.

DIMENSIONS



W	H	X	BASE MODEL NO.
8"	96"	24"	S2540-L24
8"	96"	36"	S2541-L34
8"	96"	48"	S2542-L48
8"	144"	72"	S2543-L72
8"	144"	96"	S2544-L96

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277 [Excluding Downlight]
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) with Hardware Provided

FEATURES

- Opal Matte Acrylic Cylinder
- Clear Silver Braided Cord with (1) Adjustable Aircraft Cable
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No.	+ Lamp Code	+ Finish Code	+ Option Code
S2540-L24	+ 27K	+ PT	+ OA + Option
S2541-L34	30K	XT	
S2542-L48	35K		
S2543-L72	40K		
S2544-L96			

FINISHES

PT Powder Coated Finishes*
XT Trending Brushed Metal Finishes*
*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

- BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.
- EML** Remote 10W Emergency LED Battery Backup
- OA** Specify Overall Height of Fixture in Inches; E.G. – OA48
- SWC** 45-Degree Swivel Canopy
- P38** Optional GU24 Socket for LED PAR38 Downlight 120 or 277V
- 1S** Single Stem

LIGHT OUTPUT

LXX = ~ 83 LPW Delivered Lumens (Example: L24= 24W x 83LPW = 1,992 Lumens)