

S2620 Series


Cyla 10



SUPERCEDED BY S2B80 SERIES

This product is still available to complete existing specifications, quotes, bids and active orders.
Please use the new part number for new applications and specifications.

DIMENSIONS



W	H	X	BASE MODEL NO.
10"	144"	48"	S2620-L48
10"	144"	72"	S2621-L72
10"	144"	96"	S2622-L96

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277 [Excluding Downlight]
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Matte Acrylic
- Clear Silver Braided Cord with (1) Adjustable Air Craft Cable
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No.	+	Lamp Code	+	CCT	+	Finish	+	OA	+	Option Code
S2620-L48	+	27K	+	PT	+	OA	+	Option		
S2621-L72		30K		XT						
S2622-L96		35K								
		40K								

FINISHES

PT Powder Coated Finishes*

XT Trending Brushed Metal Finishes*

*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup

OA Specify Overall Height of Fixture in Inches; E.G. – OA204

FAA Faux Alabaster Acrylic (Hand Painted) (FA1 White; FA2 Antique; FA3 Grey; FA4 Taupe; FA5 Honey; FA6 Tuscan)

SWC 35- Degree Swivel Canopy (Single Stem)

P38 Optional GU24 Socket for LED PAR38 Downlight 120 or 277V

1S Single Stem

LIGHT OUTPUT

LXX = ~ 83 LPW Delivered Lumens (Example: L48= 48W x 83LPW = 3,984 Lumens)