




DIMENSIONS



W	H	D	X	BASE MODEL NO.
24"	3 1/2"	3 1/2"	96"	S2680-L42
36"	3 1/2"	3 1/2"	96"	S2681-L72
48"	3 1/2"	3 1/2"	96"	S2682-L96
60"	3 1/2"	3 1/2"	96"	S2683-L124
72"	3 1/2"	3 1/2"	96"	S2684-L144

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Acrylic Bottom Lens
- Solid Aluminum Material
- Clear Silver Braided Cord with Adjustable Aircraft Cables
- Integral Driver
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No.	+ Lamp Code	+ CCT	+ Finish	+ OA	+ Option Code
S2680-L42	+ 27K	+ 30K	PT	+ OA	+ Option
S2681-L72	+ 30K		XT		
S2682-L96	+ 35K		CC		
S2683-L124	+ 40K				
S2684-L144					

FINISHES

PT Powder Coated Finishes*

XT Trending Brushed Metal Finishes*

CC Custom Painted Finish

*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup

MCR Multiple Canopy Mounting with Straight Cables

LIGHT OUTPUT

LXX = ~ 63 LPW Delivered Lumens (Example: L42= 42W x 63LPW = 2,646 Lumens)