


DIMENSIONS



W	H	D	X	BASE MODEL NO.
8'	3.5"	3.5"	96"	S2685-Q-L196
10'	3.5"	3.5"	96"	S2686-Q-L216
12'	3.5"	3.5"	96"	S2687-Q-L260
15'	3.5"	3.5"	96"	S2688-S-L324

Q – Indicates quartered
S – Indicates Sectioned, Not Quartered

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Acrylic Bottom Lens
- Easy Assembly
- Clear Silver Braided Cord with Adjustable Aircraft Cables (8)
- Adjustable to 96" OA
- Quartered Fixtures Help Reduce Shipping Costs
- Solid Aluminum Materials
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Finish + OA + Option Code

S2685-Q-L196	+	27K	+	PT	+	OA	+	Option
S2686-Q-L216		30K		XT				
S2687-Q-L260		35K		CC				
S2688-S-L324		40K						

FINISHES

PT Powder Coated Finishes*

XT Trending Brushed Metal Finishes*

CC Custom Painted Finish

*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)

LIGHT OUTPUT

LXX = ~ 63 LPW Delivered Lumens (Example: L144= 144W x 63LPW = 9,072 Lumens)



Spring Clip Joiner



Quarters Joined