


# S2695 Series

Grand RLM



## DIMENSIONS



W	H	X	R	BASE MODEL NO.
28"	84"	18"	2 1/4"	<b>S2695-L60M</b>
34"	84"	19"	2 5/8"	<b>S2695-34-L60M</b>
40"	84"	21 3/4"	3 1/4"	<b>S2696-L72M</b>

## SPECIFICATIONS

**Driver:** 0-10V dimming to 1%, 120/277

**Mounting:** Mounts to all Standard Electrical Junction Boxes (by others) with Hardware Provided

## FEATURES

- Available in multiple mixed color options E.G. – BL-KH (Exterior-Interior)
- Clear Silver Braided Cord with (3) Adjustable Aircraft Cables
- Integral Driver
- Opal Matte Acrylic Bottom Lens
- No Visible Hardware at the Aperture
- Heavy Gauge Spun Aluminum
- LED 0-10V Dimming Driver

## ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Exterior Finish + Interior Finish + Option Code

S2695-L60M	+ 27K	+ PT	+ PT	+ Option
S2695-34-L60M	30K	XT	XT	
S2696-L72M	35K	CC	CC	
	40K			

## FINISHES

**PT** Powder Coated Finishes\*

**XT** Trending Brushed Metal Finishes\*

**CC** Custom Painted Finish

\*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

## OPTIONS

**BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.

**EML** Remote 10W Emergency LED Battery Backup

**OA** Specify Overall Height of Fixture in Inches; E.G. – OA50

**FLL** Flush Lens (No Interior Trim) 1/2" Regress

**BK3** Black Cord with (3) Adjustable Aircraft Cables

**WH3** White Cord with (3) Adjustable Aircraft Cables

## LIGHT OUTPUT

**LXX** = ~ 85 LPW Delivered Lumens (Example: L60M= 60W x 85LPW = 5,100 Lumens)