

S2870 Series


Cyla 4



SUPERCEDED BY S2B50 SERIES

This product is still available to complete existing specifications, quotes, bids and active orders.
Please use the new part number for new applications and specifications.

DIMENSIONS



W	H	X	BASE MODEL NO.
4"	96"	12"	S2870-L12
4"	96"	24"	S2871-L24
4"	96"	36"	S2872-L36
4"	96"	48"	S2873-L48
4"	96"	60"	S2874-L60
4"	96"	72"	S2875-L72

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277 [Excluding Downlight]
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) with Hardware Provided

FEATURES

- Opal Matte Acrylic Cylinder
- Clear Silver Braided Cord with (1) Adjustable Aircraft Cable
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Finish + OA + Option Code

S2870-L12	+	27K	+	PT	ZT	+	OA	+	Option
S2871-L24		30K		BA	CT				
S2872-L36		35K		BB	TT				
S2873-L48		40K		BN	PWT				
S2874-L60				NT	BST				
S2875-L72				GT	CC				

FINISHES

BA Brushed Aluminum	CT Copper Touch
BB Brushed Brass	TT Toffee Touch
BN Brushed Nickel	PWT Pewter Touch
NT Nickel Touch	BST Blackened Steel Touch
GT Gold Touch	CC Custom Painted Finish
ZT Bronze Touch	PT Powder Coated Finishes*

*(Specify Color Code from the list of Powder Coating Finishes)

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.
EML Remote 10W Emergency LED Battery Backup
OA Specify Overall Height of Fixture in Inches; E.G. – OA48
SWC 45-Degree Swivel Canopy
1S Single Stem

LIGHT OUTPUT

LXX = ~ 109.5 LPW Delivered Lumens (Example: L24= 24W x 109.5LPW = 2,628 Lumens)

