

S2870 Series


Cyla 4



SUPERCEDED BY S2B50 SERIES

This product is still available to complete existing specifications, quotes, bids and active orders.
Please use the new part number for new applications and specifications.

DIMENSIONS



W	H	X	BASE MODEL NO.
4"	96"	12"	S2870-L12
4"	96"	24"	S2871-L24
4"	96"	36"	S2872-L36
4"	96"	48"	S2873-L48
4"	96"	60"	S2874-L60
4"	96"	72"	S2875-L72

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277 [Excluding Downlight]
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) with Hardware Provided

FEATURES

- Opal Matte Acrylic Cylinder
- Clear Silver Braided Cord with (1) Adjustable Aircraft Cable
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No.	+ Lamp Code	+ Finish	+ OA	+ Option Code
S2870-L12	27K	PT	OA	Option
S2871-L24	30K	XT		
S2872-L36	35K	CC		
S2873-L48	40K			
S2874-L60				
S2875-L72				

FINISHES

PT Powder Coated Finishes*
XT Trending Brushed Metal Finishes*
CC Custom Painted Finish
*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.
EML Remote 10W Emergency LED Battery Backup
OA Specify Overall Height of Fixture in Inches; E.G. – OA48
SWC 45-Degree Swivel Canopy
1S Single Stem

LIGHT OUTPUT

LXX = ~ 109.5 LPW Delivered Lumens (Example: L24= 24W x 109.5LPW = 2,628 Lumens)