




DIMENSIONS



W	H	X	BASE MODEL NO.
4 1/2"	96"	24"	S2910-L24
4 1/2"	96"	36"	S2911-L36
4 1/2"	96"	48"	S2912-L48
4 1/2"	120"	72"	S2913-L72
4 1/2"	144"	96"	S2914-L96

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277 [Excluding Downlight]
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) with Hardware Provided

FEATURES

- Opal Matte Acrylic Rectilinear Shade
- Clear Silver Braided Cord with (2) Adjustable Aircraft Cable
- Downlight and Core Light May Be Wired to Separate Control Circuits
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No.	+ Downlight	+ Lamp Code	+ Finish	+ OA	+ Option Code
S2910-L24	+ _____*	+ 27K	+ PT	+ OA	+ Option
S2911-L36	D16N	30K	XT		
S2912-L48	D16M	35K	PF		
S2913-L72	D16W	40K	CC		
S2914-L96					

* = if left blank – no downlight

FINISHES

- PT Powder Coated Finishes*
 - XT Trending Brushed Metal Finishes*
 - PF Pure Metal Finishes*
 - CC Custom Painted Finish
- *(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

DOWNLIGHT OPTIONS

- D16N Narrow (30 degrees)
- D16M Medium (45 degrees)
- D16W Wide (60 degrees)

OPTIONS

- BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.
- EML Remote 10W Emergency LED Battery Backup
- OA Specify Overall Height of Fixture in Inches; E.G. – OA48
- SWC 45-Degree Swivel Canopy
- 1S Single Stem
- BK2 – Black Cord with (2) Adjustable Aircraft Cable
- WH2 – White Cord with (2) Adjustable Aircraft Cable

LIGHT OUTPUT

LXX = ~ 93 LPW Delivered Lumens (Example: L24= 24W x 93LPW = 2,232 Lumens)

Downlight Lumens: DxxW indicates Downlight wattage and beam spread. For the downlight, typical lumen output is 100LPW, so a D16W would deliver 1,600L in a wide beam pattern.