


S2A00 Series

Eclipse



DIMENSIONS



W	H	X	BASE MODEL NO.
14"	60"	14 3/4"	S2A00-L24
18"	60"	18 3/4"	S2A01-L32
18"	60"	18 3/4"	S2A01-L52
22"	60"	22 3/4"	S2A02-L48

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Clear Silver Braided Cord with Adjustable Aircraft Cable
- Opal Matte Acrylic
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Finish + OA + Option Code

Model No.	Lamp Code	Finish	OA	Option Code
S2A00-L24	+ 27K	+ PT	+ OA	+ Option
S2A01-L32	30K	XT		
S2A01-L52	35K	CC		
S2A02-L48	40K			

FINISHES

PT Powder Coated Finishes*

XT Trending Brushed Metal Finishes*

CC Custom Painted Finish

*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML – Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)

1S – Single Stem

LIGHT OUTPUT

LXX = ~ 95 LPW Delivered Lumens (Example: L24= 24W x 95LPW = 2,280 Lumens)