


S2A30 Series

Mezzo 4



DIMENSIONS



W	H	D	X	BASE MODEL NO.
36"	4-1/4"	4-1/4"	48"	S2A31-L144-72U
48"	4-1/4"	4-1/4"	48"	S2A32-L192-96U
60"	4-1/4"	4-1/4"	48"	S2A33-L248-124U
72"	4-1/4"	4-1/4"	48"	S2A34-L288-144U

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Larger units require additional structural blocking.

FEATURES

- High Transmission Opal Lens in both Direct and Indirect positions
- Extruded Aluminum Housing
- Clear Silver Braided Cord with Adjustable Aircraft Cables
- Integral Driver
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + OA + Option Code

S2A31-L144-72U	+	27K	+	PT	+	OA	+	Option
S2A32-L192-96U		30K		CC				
S2A33-L248-124U		35K		BA				
S2A34-L288-144U		40K		NT				
				GT				
				CT				
				ZT				
				PWT				
				BST				

FINISHES

BA Brushed Aluminum	PWT Pewter Touch
ZT Bronze Touch	BST Blackened Steel Touch
NT Nickel Touch	CC Custom Painted Finish
GT Gold Touch	PT Powder Coated Finishes*
CT Copper Touch	

*(Specify Color Code from the list of Powder Coating Finishes)

OPTIONS

- BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.
- EML** Remote 10W Emergency LED Battery Backup
- MCR** Minimal Canopy – Remote Driver Option (4 Vertical Cables)
- 2C** 2 Circuit – Direct/Indirect Separately Switched
- OA** Specify Overall Height of Fixture in Inches; E.G. – OA48

LIGHT OUTPUT

LXX = ~ 70 LPW Down and ~ 78LPW Up Delivered Lumens
 (Example: L84= 84 x 70 = 5,880 Lumens Down and L42= 42 x 78 = 3,276 Lumens Up)