




## DIMENSIONS



W	H	D	X	BASE MODEL NO.
36"	4-1/4"	4-1/4"	48"	<b>S2A31-L144-72U</b>
48"	4-1/4"	4-1/4"	48"	<b>S2A32-L192-96U</b>
60"	4-1/4"	4-1/4"	48"	<b>S2A33-L248-124U</b>
72"	4-1/4"	4-1/4"	48"	<b>S2A34-L288-144U</b>

## SPECIFICATIONS

**Driver:** 0-10V dimming to 1%, 120/277

**Mounting:** Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Larger units require additional structural blocking.

## FEATURES

- High Transmission Opal Lens in both Direct and Indirect positions
- Extruded Aluminum Housing
- Clear Silver Braided Cord with Adjustable Aircraft Cables
- Integral Driver
- LED 0-10V Dimming Driver

## ORDER AS A COMPLETE UNIT:

**Model No. + Lamp Code + CCT + Finish + OA + Option Code**  
 S2A31-L144-72U + 27K + PT + OA + Option  
 S2A32-L192-96U 30K XT  
 S2A33-L248-124U 35K CC  
 S2A34-L288-144U 40K

## FINISHES

**PT** Powder Coated Finishes\*

**XT** Trending Brushed Metal Finishes\*

**CC** Custom Painted Finish

\*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

## OPTIONS

**BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.

**EML** Remote 10W Emergency LED Battery Backup

**MCR** Minimal Canopy – Remote Driver Option (4 Vertical Cables)

**2C** 2 Circuit – Direct/Indirect Separately Switched

**OA** Specify Overall Height of Fixture in Inches; E.G. – OA48

## LIGHT OUTPUT

**LXX** = ~ 70 LPW Down and ~ 78LPW Up Delivered Lumens (Example: L84= 84 x 70 = 5,880 Lumens Down and L42= 42 x 78 = 3,276 Lumens Up)