


S2A75 Series

Formoso



DIMENSIONS



X	Diffuser Qty	H	Dia	BASE MODEL NO.
10 5/8"	1	60"	4"	S2A75-L12
22 3/4"	2	60"	4"	S2A76-L24
34 7/8"	3	60"	4"	S2A77-L36

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opalized Curved Glass Cylinders
- Aluminum Construction
- Driver integral in the canopy
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + Option Code

S2A75-L12	+	27K	+	PT	ZT	+	Option
S2A76-L24		30K		BA	CT		
S2A77-L36		35K		BB	TT		
		40K		BN	PWT		
				NT	BST		
				GT	CC		

FINISHES

BA Brushed Aluminum	CT Copper Touch
BB Brushed Brass	TT Toffee Touch
BN Brushed Nickel	PWT Pewter Touch
NT Nickel Touch	BST Blackened Steel Touch
GT Gold Touch	CC Custom Painted Finish
ZT Bronze Touch	PT Powder Coated Finishes*

*(Specify Color Code from the list of Powder Coating Finishes)

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)

OA Specify Overall Height of Fixture in Inches; E.G. – OA48

LIGHT OUTPUT

LXX = ~ 80 LPW Delivered Lumens (Example: L12= 12W x 80LPW = 960 Lumens)