S2A95 Series
Vaso

DIMENSIONS



Dia	H	X	BASE MODEL NO.
6″	60″	9.5″	**S2A95-L16-D12**

FEATURES

Drivers: 0-10V dimming to 1%, 120/277 for both Cylinder and Downlight (on separate circuits)
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) with Hardware Provided

FEATURES

- Clear Silver Braided Cord with (1) Adjustable Aircraft Cable
- LED 0-10V Dimming Drivers

ORDER AS A COMPLETE UNIT:

Model No. + Downlight Option + Lamp Code + Finish + OA + Option Code

S2A95-L16-D12	+	N	+	27K	+	PT	ZT	+	Option
		M		30K		BA	PWT		
		W		35K		NT	BST		
				40K		GT	CC		
						CT			

FINISHES

BA Brushed Aluminum
NT Nickel Touch
GT Gold Touch
CT Copper Touch
ZT Bronze Touch
PWT Pewter Touch
BST Blackened Steel Touch
CC Custom Painted Finish
PT Powder Coated Finishes*
*(Specify Color Code from the list of Powder Coating Finishes)

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.
EML Remote 10W Emergency LED Battery Backup
OA Specify Overall Height of Fixture in Inches; E.G. – OA48
1S Single Stem

DOWNLIGHT OPTIONS

N Narrow (30 degrees)
M Medium (45 degrees)
W Wide (60 degrees)

LIGHT OUTPUT

LXX = ~ 100 LPW Cylinder + ~90LPW (Downlight) Delivered Lumens (Example: [L16= 16W x 100LPW = 1,600 Lumens] + [D12= 12W x 90LPW = 1,080 Lumens] = 2,680 Total Lumens)

www.ScottArchLighting.com | Tel (707) 864-2172 | Fax (707) 864-2182
© Copyright 2024 Scott Architectural Lighting. All Rights Reserved. Made in the USA.