


S2B40 Series

Cyla 3



DIMENSIONS



W	H	X	BASE MODEL NO.
3"	96"	12"	S2B40-L12
3"	96"	24"	S2B41-L24
3"	96"	36"	S2B42-L36
3"	96"	48"	S2B43-L48
3"	120"	60"	S2B44-L60
3"	120"	72"	S2B45-L72

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277 [Excluding Downlight]
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) with Hardware Provided

FEATURES

- Opal Matte Acrylic Cylinder
- Clear Silver Braided Cord with (1) Adjustable Aircraft Cable
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No.	+ Lamp Code	+ Finish	+ OA	+ Option Code
S2B40-L12	+ 27K	+ PT	+ OA	+ Option
S2B41-L24	30K	XT		
S2B42-L36	35K	CC		
S2B43-L48	40K			
S2B44-L60				
S2B45-L72				

FINISHES

- PT Powder Coated Finishes*
 - XT Trending Brushed Metal Finishes*
 - CC Custom Painted Finish
- *(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

- BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.
- EML Remote 10W Emergency LED Battery Backup
- 1S Single Stem

LIGHT OUTPUT

LXX = ~ 105 LPW Delivered Lumens (Example: L24= 24 x 105 = 2,520 Lumens)

