


DIMENSIONS



W	H	X	BASE MODEL NO.
4"	96"	12"	<b>S2B50-L12</b>
4"	96"	24"	<b>S2B51-L24</b>
4"	96"	36"	<b>S2B52-L36</b>
4"	96"	48"	<b>S2B53-L48</b>
4"	96"	60"	<b>S2B54-L60</b>
4"	120"	72"	<b>S2B55-L72</b>
4"	120"	96"	<b>S2B56-L96</b>

SPECIFICATIONS

**Drivers:** 0-10V dimming to 1%, 120/277 for both Cylinder and Downlight (on separate circuits)

**Mounting:** Mounts to all Standard Electrical Junction Boxes (by others) with Hardware Provided

FEATURES

- Opal Matte Acrylic Cylinder
- Clear Silver Braided Cord with (1) Adjustable Aircraft Cable
- Downlight and Cylinder Core May Be Wired to Separate Control Circuits
- Drivers Mounted in Canopy
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No.	+ Downlight	+ Lamp Code	+ Finish	+ OA	+ Option Code
S2B50-L12	+ _____*	+ 27K	+ PT	+ OA	+ Option
S2B51-L24	D12N	30K	XT		
S2B52-L36	D12M	35K	CC		
S2B53-L48	D12W	40K			
S2B54-L60					
S2B55-L72					
S2B56-L96					

\_\_\_\_\_\* = if left blank – no downlight

FINISHES

PT Powder Coated Finishes\*

XT Trending Brushed Metal Finishes\*

CC Custom Painted Finish

\*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

DOWNLIGHT OPTIONS

- D12N Narrow (30 degrees)
- D12M Medium (45 degrees)
- D12W Wide (60 degrees)

OPTIONS

**BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.

**EML** Remote 10W Emergency LED Battery Backup

**OA** Specify Overall Height of Fixture in Inches; E.G. – OA48

**1S** Single Stem

**BK1** Black Cord with (1) Adjustable Aircraft Cables

**WH1** White Cord with (1) Adjustable Aircraft Cables

LUMENS

**Cylinder Core Lighting Lumens:** LXX = LED Wattage, therefore L24 = LED 24W. The typical lumen output is ~109LPW, so therefore L24 would deliver 2,616L. Use this formula to estimate delivered lumens based on the LXX number for each length.

**Downlight Lumens:** DxxW indicates Downlight wattage and beam spread. For the downlight, typical lumen output is 100LPW, so a D12W would deliver 1,200L in a wide beam pattern.