S3505 Series

DIMENSIONS



W	H	D	MC	BASE MODEL NO.
7″	24″	4″	9 1/2″	**S3505-L16**

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Matte Acrylic
- ADA Compliant
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + Option Code

S3505-L16	+	27K 30K 35K 40K	+	PT BA BB BC BN	PB PC PN	+	Option

FINISHES

BA Brushed Aluminum
BB Brushed Brass
BC Brushed Chrome
BN Brushed Nickel
PB Polished Brass
PC Polished Chrome
PN Polished Nickel
PT Powder Coated Finishes*
*(Specify Color Code from the list of Powder Coating Finishes)

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.
EML Remote 10W Emergency LED Battery Backup
TPL Top Lens
FAA Faux Alabaster Acrylic (Hand Painted) [FA1 White; FA2 Antique; FA3 Grey; FA4 Taupe; FA5 Honey; FA6 Tuscan]

LIGHT OUTPUT

LXX = ~ 75 LPW Delivered Lumens (Example: L16= 16W x 75LPW = 1,200 Lumens)

www.ScottArchLighting.com | Tel (707) 864-2172 | Fax (707) 864-2182
© Copyright 2024 Scott Architectural Lighting. All Rights Reserved. Made in the USA.