S3875 Series

DIMENSIONS



W	H	D	MC	BASE MODEL NO.
25 1/4″	4 5/8″	3″	12 5/8″	**S3875-L18**
37 1/4″	4 5/8″	3 5/8″	18 5/8″	**S3876-L24**
49″	4 5/8″	3 7/8″	24 1/2″	**S3877-L32**

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Matte Acrylic
- Solid Aluminum End Caps
- ADA Compliant
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + Option Code

S3875-L18	+	27K	+	PT	+	Option
S3876-L24		30K		BA		
S3877-L32		35K		BB		
		40K		BC		
				BN		

FINISHES

BA Brushed Aluminum
BB Brushed Brass
BC Brushed Chrome
BN Brushed Nickel
PT Powder Coated Finishes*
*(Specify Color Code from the list of Powder Coating Finishes)

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.
EML Remote 10W Emergency LED Battery Backup
FAA Faux Alabaster Acrylic (Hand Painted) [FA1 White; FA2 Antique; FA3 Grey; FA4 Taupe; FA5 Honey; FA6 Tuscan]

LIGHT OUTPUT

LXX = ~ 69 LPW Delivered Lumens (Example: L18= 18W x 69LPW = 1,242 Lumens)

www.ScottArchLighting.com | Tel (707) 864-2172 | Fax (707) 864-2182
© Copyright 2024 Scott Architectural Lighting. All Rights Reserved. Made in the USA.