S7135 Series

DIMENSIONS



W	H	BASE MODEL NO.
6 1/4″	9 1/8″	**S7135-L18**

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Matte Acrylic
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + Option Code

S7135-L18	+	27K 30K 35K 40K	+	PT XT PF	+	Option

FINISHES

PT Powder Coated Finishes*
XT Trending Brushed Metal Finishes*
PF Pure Metal Finishes*
*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.
EML Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)
FAA Faux Alabaster Acrylic (Hand Painted) [FA1 White; FA2, Antique; FA3 Grey; FA4 Taupe; FA5 Honey, FA6 Tuscan]
WOG Opal Glass

LIGHT OUTPUT

LXX = ~ 69 LPW Delivered Lumens (Example: L18= 18W x 69LPW = 1,242 Lumens)

www.ScottArchLighting.com | Tel (707) 864-2172 | Fax (707) 864-2182
© Copyright 2025 Scott Architectural Lighting. All Rights Reserved. Made in the USA.