




DIMENSIONS



W	H	X	BASE MODEL NO.
18"	12"	7 1/2"	S7200-L36
24"	14 1/2"	10"	S7201-L60

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Matte Acrylic Bottom Diffuser
- Fabric shades on heavy Translucent White styrene
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish Code + Fabric Code + Option Code

S7200-L36	+	27K	+	PT	+	LF01	LF08	+	Option
S7201-L60		30K		XT		LF02	LF09		
		35K				LF03	LF10		
		40K				LF04	LF11		
						LF05	LF12		
						LF06	LF13		
						LF07	LF14		

FINISHES

PT Powder Coated Finishes*

XT Trending Brushed Metal Finishes*

*(Specify Color Code from the list of Finishes – ie. Gold Touch would be 'GT')

FABRIC

LF01 Huggy White	LF02 Olive
LF03 Sage	LF04 Orchre
LF05 Praline	LF07 Canvas
LF08 Butter	LF09 Breeze
LF10 Ebony	LF11 Parchment
LF12 Flan	LF13 Natural HF
LF14 Merlot	
CLF Custom Linen Fabric Shade (Consult Factory)	

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)

LIGHT OUTPUT

LXX = ~ 63 LPW Delivered Lumens (Example: L36= 36W x 63LPW = 2,268 Lumens – Varies with Shade Color)