




## DIMENSIONS



W	H	D	MC	BASE MODEL NO.
11"	11 1/2"	5"	6"	<b>S9025-L16</b>
14"	16"	10"	6 7/8"	<b>S9026-L18</b>

## SPECIFICATIONS

**Driver:** 0-10V dimming to 1%, 120/277

**Mounting:** Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Silicone Seal Required (by others).

## FEATURES

- Opal Acrylic Panels Standard
- UL Listed for Wet Location
- LED 0-10V Dimming Driver

## ORDER AS A COMPLETE UNIT:

Model No.	+	Lamp Code	+	CCT	+	Finish	+	Option Code
S9025-L16	+	27K	+	PT	+	Option		
S9026-L18		30K		SD				
		35K		XT				
		40K						

## FINISHES

**PT** Powder Coated Finishes\*

**SD** Shimmer Dimensional Metallic Finishes\*

**XT** Trending Brushed Metal Finishes\*

\*(Specify Color Code from the list of Finishes [except interior only metallics] – ie. Gold Touch would be 'GT')

## OPTIONS

**BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.

**EML** Remote 10W Emergency LED Battery Backup

**SG** Seedy Glass

**WOG** Opal Glass

## LIGHT OUTPUT

**LXX** = ~ 74 LPW Delivered Lumens (Example: L16= 16W x 74LPW = 1,184 Lumens)