




DIMENSIONS



W	H	D	MC	BASE MODEL NO.
10 1/2"	11 1/2"	5 1/4"	5 5/8"	S9030-L16
12"	14"	8"	7"	S9031-L18

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Silicone Seal Required (by others).

FEATURES

- Opal Acrylic Panels Standard
- UL Listed for Wet Location
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No.	+	Lamp Code	+	CCT	+	Finish	+	Option Code
S9030-L16	+	27K	+	PT	+	Option		
S9031-L18		30K		SD				
		35K		XT				
		40K						

FINISHES

PT Powder Coated Finishes*

SD Shimmer Dimensional Metallic Finishes*

XT Trending Brushed Metal Finishes*

*(Specify Color Code from the list of Finishes [except interior only metallics] – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup

SG Seedy Glass

WOG Opal Glass

LIGHT OUTPUT

LXX = ~ 70 LPW Delivered Lumens (Example: L16 = 16W x 70LPW = 1,120 Lumens)