


## DIMENSIONS



W	H	D	MC	BASE MODEL NO.
7"	16"	4"	8"	<b>S9110-L24</b>
9"	20"	5 1/2"	10"	<b>S9111-L32</b>

## SPECIFICATIONS

**Driver:** 0-10V dimming to 1%, 120/277

**Mounting:** Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Silicone Seal Required (by others).

## FEATURES

- Opal Acrylic Lens
- Opal Acrylic Top & Bottom Lens
- Solid Bar Stock Material
- UL Listed for Wet Location
- LED 0-10V Dimming Driver

## ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + Option Code

S9110-L24	+	27K	+	PT	+	Option
S9111-L32		30K		SD		
		35K		PF		
		40K		XT		

## FINISHES

**PT** Powder Coated Finishes\*

**SD** Shimmer Dimensional Metallic Finishes\*

**PF** Pure Metal Finishes\*

**XT** Trending Brushed Metal Finishes\*

\*(Specify Color Code from the list of Finishes [except interior only metallics] – ie. Gold Touch would be 'GT')

## OPTIONS

**BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.

**EML** Remote 10W Emergency LED Battery Backup

## LIGHT OUTPUT

**LXX** = ~ 76 LPW Delivered Lumens (Example: L24= 24W x 76LPW = 1,824 Lumens)