




DIMENSIONS



| W | H | D | MC | BASE MODEL NO. |
|----|-----|----|----|------------------|
| 8" | 18" | 7" | 7" | S9210-L24 |

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Silicone Seal Required (by others).

FEATURES

- Opal Acrylic Panels
- UL Listed for Wet Location
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + Option Code
 S9210-L24 + 27K + 30K + PT + Option
 35K
 40K
 SD
 XT

FINISHES

- PT Powder Coated Finishes*
- SD Shimmer Dimensional Metallic Finishes*
- XT Trending Brushed Metal Finishes*

*(Specify Color Code from the list of Finishes [except interior only metallics] – ie. Gold Touch would be 'GT')

OPTIONS

- BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.
- EML Remote 10W Emergency LED Battery Backup

LIGHT OUTPUT

LXX = ~ 61 LPW Delivered Lumens (Example: L24= 24W x 61LPW = 1,464 Lumens)