




## DIMENSIONS



W	H	D	MC	BASE MODEL NO.
15"	30"	7 1/2"	15"	<b>S9290-L34</b>
15"	42"	7 1/2"	21"	<b>S9291-L60</b>
15"	54"	7 1/2"	26"	<b>S9292-L72</b>

## SPECIFICATIONS

**Driver:** 0-10V dimming to 1%, 120/277

**Mounting:** Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Silicone Seal Required (by others).

## FEATURES

- Opal Acrylic Lens
- Solid Aluminum Bar Stock Material
- Stainless Steel Fastener
- UL Listed for Wet Location
- LED 0-10V Dimming Driver

## ORDER AS A COMPLETE UNIT:

**Model No. + Lamp Code + CCT + Finish + Option Code**

S9290-L34	+	27K	+	PT	+	Option
S9291-L60		30K		SD		
S9292-L72		35K		XT		
		40K				

## FINISHES

**PT** Powder Coated Finishes\*

**SD** Shimmer Dimensional Metallic Finishes\*

**XT** Trending Brushed Metal Finishes\*

\*(Specify Color Code from the list of Finishes [except interior only metallics] – ie. Gold Touch would be 'GT')

## OPTIONS

**BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.

**EML** Remote 10W Emergency LED Battery Backup

## LIGHT OUTPUT

**LXX** = ~ 72 LPW Delivered Lumens (Example: L34= 34W x 72LPW = 2,448 Lumens)