




DIMENSIONS



SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277 Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Silicone Seal Required (by others).

FEATURES

- Opal Matte Acrylic Lens
- Solid Aluminum Material
- UL Listed for Wet Location
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + Option Code							
S9300-L14 S9301-L18	+	27K 30K 35K 40K	+	PT BA	+	Option	

FINISHES

BA Brushed Aluminum PT Powder Coated Finishes*

*(Specify Color Code from the list of Powder Coating Finishes [except interior only metallics])

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant. EML Remote 10W Emergency LED Battery Backup

LIGHT OUTPUT

LXX = ~ 55 LPW Delivered Lumens (Example: L14= 14W x 55LPW = 770 Lumens)

** Try our new **Shimmer Metalic Paints**, Formulated for Exterior Conditions.

www.ScottArchLighting.com | Tel (707) 864-2172 | Fax (707) 864-2182 © Copyright 2024 Scott Architectural Lighting. All Rights Reserved. Made in the USA.

