








DIMENSIONS



| W | Н | D | MC | BASE MODEL NO. |
|----|-----|----|---------|----------------|
| 6" | 21" | 4" | 10.5" | S9302-L14 |
| 6" | 27" | Δ" | 13 1/2" | S9303-I 18 |

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Silicone Seal Required (by others).

FEATURES

- Opal Matte Acrylic Lens
- Solid Aluminum Material
- UL Listed for Wet Location
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + Option Code

FINISHES

BA Brushed Aluminum PT Powder Coated Finishes*

*(Specify Color Code from the list of Powder Coating Finishes [except interior only metallics])

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup

LIGHT OUTPUT

LXX = ~ 55 LPW Delivered Lumens (Example: L14= 14W x 55LPW = 770 Lumens)

** Try our new **Shimmer Metalic Paints**, Formulated for Exterior Conditions.





