


DIMENSIONS



W	H	D	MC	BASE MODEL NO.
7 1/4"	20 3/4"	4"	10 3/8"	S9320-L24
7 1/4"	26 3/4"	4"	13 3/8"	S9321-L32

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Silicone Seal Required (by others).

FEATURES

- Opal Acrylic Lens
- Solid Aluminum Bar Stock Material
- Solid Aluminum End-Caps
- UL Listed for Wet Location
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + Option Code

S9320-L24	+	27K	+	PT	+	Option
S9321-L32		30K		SD		
		35K		XT		
		40K				

FINISHES

PT Powder Coated Finishes*

SD Shimmer Dimensional Metallic Finishes*

XT Trending Brushed Metal Finishes*

*(Specify Color Code from the list of Finishes [except interior only metallics] – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup

LIGHT OUTPUT

LXX = ~ 75 LPW Delivered Lumens (Example: L24= 24W x 75LPW = 1,800 Lumens)