




DIMENSIONS



W	H	D	MC	BASE MODEL NO.
14"	14"	6"	7"	S9340-L36

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Silicone Seal Required (by others).

FEATURES

- Opal Acrylic Lens
- Solid Aluminum Material
- Solid Aluminum Top
- Stainless Steel Fastener
- UL Listed for Wet Location
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + Option Code
 S9340-L36 + 27K + 30K + 35K + 40K + PT / SD + Option

FINISHES

PT Powder Coated Finishes*

SD Shimmer Dimensional Metallic Finishes*

*(Specify Color Code from the list of Finishes [except interior only metallics] – ie. Gold Touch would be 'GT')

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup

LIGHT OUTPUT

LXX = ~ 62 LPW Delivered Lumens (Example: L36= 36W x 62LPW = 2,232 Lumens)