




DIMENSIONS



| W | H | D | MC | BASE MODEL NO. |
|----|-----|----|---------|------------------|
| 6" | 21" | 4" | 10 1/2" | S9365-L12 |
| 6" | 27" | 4" | 13 1/2" | S9366-L16 |

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Silicone Seal Required (by others).

FEATURES

- Opal Acrylic Lens
- Solid Aluminum Bar Stock Material
- UL Listed for Wet Location
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

| Model No. | + | Lamp Code | + | CCT | + | Finish | + | Option Code |
|-----------|---|-----------|---|-----|---|--------|---|-------------|
| S9365-L12 | + | 27K | + | PT | + | Option | | |
| S9366-L16 | | 30K | | SD | | | | |
| | | 35K | | XT | | | | |
| | | 40K | | | | | | |

FINISHES

- PT** Powder Coated Finishes*
- SD** Shimmer Dimensional Metallic Finishes*
- XT** Trending Brushed Metal Finishes*

*(Specify Color Code from the list of Finishes [except interior only metallics] – ie. Gold Touch would be 'GT')

OPTIONS

- BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.
- EML** Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)

LIGHT OUTPUT

LXX = ~ 75 LPW Delivered Lumens (Example: L12= 12W x 75LPW = 900 Lumens)