




DIMENSIONS



W	H	D	MC	BASE MODEL NO.
6"	18"	7"	9"	S9830-L24
6"	24"	7"	12"	S9381-L32

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Silicone Seal Required (by others).

FEATURES

- Opal Acrylic Lens
- Bar Stock Trim
- Die-Cast End Caps
- UL Listed for Wet Locations
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + Option Code

S9380-L24	+	27K	+	PT	+	Option
S9381-L32		30K		CC		
		35K		BA		
		40K		NT		
				GT		
				CT		

FINISHES

BA Brushed Aluminum **CT** Copper Touch
NT Nickel Touch **CC** Custom Painted Finish
GT Gold Touch **PT** Painted Finishes*
 *(Specify Color Code from the list of Powdercoat finishes [except interior only metallics])

OPTIONS

EML Emergency Battery Pack with LED Lighting (Remote – Requires Additional Power Cable)

LIGHT OUTPUT

LXX = ~ 89 LPW Delivered Lumens (Example: L24= 24 x 89 = 2,136 Lumens)

** Try our new **Shimmer Metallic Paints**, Formulated for Exterior Conditions.